

	Clamping range:	Band width:	Band Thickness:	Wormdrive housing		Hexagon head Screw					Thightening Torque:	Breaking Torque:
	D	B1+/-1	S1	B2	H1	H2	H3	N	S2	T		
				max.	max	+/-0,3	min	+0,3-0,6	H13	+/-0,3	AD*	PD**
	8-14	9 (1)	0,5	14	14	8	4	1,2	7	1,6	3Nm	4Nm
	11-17	9 (1)	0,5	14	14	8	4	1,2	7	1,6	3Nm	4Nm
	13-20	9 (1)	0,5	14	14	8	4	1,2	7	1,6	3Nm	4Nm
	15-25	12	0,5	20	16	8	4	1,2	7	1,6	5Nm	6,5Nm
	19-29	12	0,5	20	16	8	4	1,2	7	1,6	5Nm	6,5Nm
	22-32	12	0,5	20	16	8	4	1,2	7	1,6	5Nm	6,5Nm
	26-38	12	0,5	20	16	8	4	1,2	7	1,6	5Nm	6,5Nm
	32-44	12	0,5	20	16	8	4	1,2	7	1,6	5Nm	6,5Nm
	38-50	12	0,5	20	16	8	4	1,2	7	1,6	5Nm	6,5Nm
	44-56	12	0,5	20	16	8	4	1,2	7	1,6	5Nm	6,5Nm
	50-65	12	0,5	20	16	8	4	1,2	7	1,6	5Nm	6,5Nm
	58-75	12	0,5	20	16	8	4	1,2	7	1,6	5Nm	6,5Nm
	68-85	12	0,5	20	16	8	4	1,2	7	1,6	5Nm	6,5Nm
	77-95	12	0,5	20	16	8	4	1,2	7	1,6	5Nm	6,5Nm
	87-112	12	0,5	20	16	8	4	1,2	7	1,6	5Nm	6,5Nm
	104-138	12	0,5	20	16	8	4	1,2	7	1,6	5Nm	6,5Nm
	130-165	12	0,5	20	16	8	4	1,2	7	1,6	5Nm	6,5Nm
	155-180	12	0,5	20	16	8	4	1,2	7	1,6	5Nm	6,5Nm
	175-205	12	0,5	20	16	8	4	1,2	7	1,6	5Nm	6,5Nm
	200-231	12	0,5	20	16	8	4	1,2	7	1,6	5Nm	6,5Nm
	226-256	12	0,5	20	16	8	4	1,2	7	1,6	5Nm	6,5Nm
	251-282	12	0,5	20	16	8	4	1,2	7	1,6	5Nm	6,5Nm
	277-307	12	0,5	20	16	8	4	1,2	7	1,6	5Nm	6,5Nm
	302-325	12	0,5	20	16	8	4	1,2	7	1,6	5Nm	6,5Nm
321-350	12	0,5	20	16	8	4	1,2	7	1,6	5Nm	6,5Nm	
346-375	12	0,5	20	16	8	4	1,2	7	1,6	5Nm	6,5Nm	
371-400	12	0,5	20	16	8	4	1,2	7	1,6	5Nm	6,5Nm	
396-425	12	0,5	20	16	8	4	1,2	7	1,6	5Nm	6,5Nm	
AD*= Maximum advised torque.					PD**= Minimum test torque in: Nm according to DIN 3017-1.							
Material code	Hexagon head screw			Wormdrive housing				Band				
W1	Steel (according to the choice of the manufacturer)							Steel with minimum tensile strength of 400 N/mm2 ((1) aisi 430 or higher)				
W2	Steel according to nr. 1.4301 DIN EN 10088-2 or material with similar corrosion resistance (according to the choice of the manufacturer)											
W3	Steel according to nr. 1.4401 DIN EN 10088-2 or material with similar corrosion resistance(according to the choice of the manufacturer)											